



OUTDOOR PHOTOMETRIC REPORT

CATALOG: OU





MANUFACTURER: PRO-LIGHT
 TEST #: OU
 TEST LAB: 1
 DESCRIPTION:
 LAMP: G1013
 LAMP OUTPUT: 1 LAMP, RATED LUMENS/LAMP: 21
 INPUT WATTAGE: 3
 LUMINOUS OPENING: POINT
 MAX CD: 25.8 AT HORIZONTAL: 90°, VERTICAL: 0°
 CUTOFF CLASS: FULL CUTOFF
 ROADWAY CLASS: VERY SHORT, TYPE I
 EFFICIENCY: 1.6%

No
 Photo
 Available



VISUAL PHOTOMETRIC TOOL 1.2.46 COPYRIGHT 2017, ACUITY BRANDS LIGHTING.
 THIS PHOTOMETRIC REPORT HAS BEEN GENERATED USING METHODS RECOMMENDED BY THE IESNA. CALCULATIONS ARE BASED ON PHOTOMETRIC DATA PROVIDED BY THE MANUFACTURER, AND THE ACCURACY OF THIS PHOTOMETRIC REPORT IS DEPENDENT ON THE ACCURACY OF THE DATA PROVIDED. END-USER ENVIRONMENT AND APPLICATION (INCLUDING, BUT NOT LIMITED TO, VOLTAGE VARIATION AND DIRT ACCUMULATION) CAN CAUSE ACTUAL PHOTOMETRIC PERFORMANCE TO DIFFER FROM THE PERFORMANCE CALCULATED USING THE DATA PROVIDED BY THE MANUFACTURER. THIS REPORT IS PROVIDED WITHOUT WARRANTY AS TO ACCURACY, COMPLETENESS, RELIABILITY OR OTHERWISE. IN NO EVENT WILL ACUITY BRANDS LIGHTING BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF THIS REPORT.



ZONAL LUMEN SUMMARY

ZONE	LUMENS	% LAMP	% LUMINAIRE
0-30	0.3	1.6%	100%
0-40	0.3	1.6%	100%
0-60	0.3	1.6%	100%
60-90	0.000	0%	0%
70-100	0.000	0%	0%
90-120	0.000	0%	0%
0-90	0.3	1.6%	100%
90-180	0.000	0%	0%
0-180	0.3	1.6%	100%

LUMENS PER ZONE

ZONE	LUMENS	% TOTAL	ZONE	LUMENS	% TOTAL
0-10	0.2	70.7%	90-100	0.000	0%
10-20	0.1	16.7%	100-110	0.000	0%
20-30	0.0	12.6%	110-120	0.000	0%
30-40	0.000	0.0%	120-130	0.000	0%
40-50	0.000	0.0%	130-140	0.000	0%
50-60	0.000	0.0%	140-150	0.000	0%
60-70	0.000	0.0%	150-160	0.000	0%
70-80	0.000	0.0%	160-170	0.000	0%
80-90	0.000	0.0%	170-180	0.000	0%


ROADWAY SUMMARY

CUTOFF CLASSIFICATION:	FULL CUTOFF	
DISTRIBUTION:	TYPE I, VERY SHORT	
MAX CD, 90 DEG VERT:	0.000	
MAX CD, 80 TO <90 DEG:	0.000	
	LUMENS	% LAMP
DOWNWARD STREET SIDE:	0.2	0.9%
DOWNWARD HOUSE SIDE:	0.2	0.9%
DOWNWARD TOTAL:	0.4	1.8%
UPWARD STREET SIDE:	0.000	0%
UPWARD HOUSE SIDE:	0.000	0%
UPWARD TOTAL:	0.000	0%
TOTAL LUMENS:	0.4	1.8%

LCS TABLE

BUG RATING	B0 - U0 - G0	
FORWARD LIGHT	LUMENS	LUMENS %
LOW(0-30):	0.2	0.9%
MEDIUM(30-60):	0.000	0%
HIGH(60-80):	0.000	0%
VERY HIGH(80-90):	0.000	0%
BACK LIGHT		
LOW(0-30):	0.2	0.9%
MEDIUM(30-60):	0.000	0%
HIGH(60-80):	0.000	0%
VERY HIGH(80-90):	0.000	0%
UPLIGHT		
LOW(90-100):	0.000	0%
HIGH(100-180):	0.000	0%
TRAPPED LIGHT:	20.6	98.2%

LCS Graph



Scale = Max LCS %

Trapped Light: 20.6lm, 98.2%

CANDELA TABLE - TYPE C

	0	90	180
0	16.2	25.8	16.2
5	0	4.8	0
10	0	0	0
15	0	0.8	0
20	0	0	0
25	0.4	0	0.4
30	0	0	0
35	0	0	0
40	0	0	0
45	0	0	0
50	0	0	0
55	0	0	0
60	0	0	0
65	0	0	0
70	0	0	0
75	0	0	0
80	0	0	0
85	0	0	0
90	0	0	0
95	0	0	0
100	0	0	0
105	0	0	0
110	0	0	0
115	0	0	0
120	0	0	0
125	0	0	0
130	0	0	0
135	0	0	0
140	0	0	0
145	0	0	0
150	0	0	0
155	0	0	0
160	0	0	0
165	0	0	0